

HELI

GEAR
Keeps you going

CBD15-170G Electric Pallet Truck

Configuration and performance

- Fork fit for reversible pallets.
- Separately excited motor, Strong climbing ability. Stepless speed control system, easy to operate.
- Battery open design, easy to replacement. Built-in charger.
- Sealed batteries free of maintenance, safe operation and no pollution.
- Small body, suitable for narrow space.
- Automatic lifting limit, safety, energy saving.
- Emergency reversing device and Emergency brake switch.
- Low noise, low energy consumption, Every day only 2kWh

Superman

Built-in charger

Free-maintained battery

Fork suitable for reversible pallet



Feature		
Model		CBD15-170G
Loading capacity	kg	1500
Load center	mm	600
Wheel base	mm	1301
Operating type		Walkie
Wheels		
Wheels type		PU
Wheel quantity Driving wheel/Balance wheel/Bearing wheel		1/0/4
Driving wheel size	mm	∅252×67
Bearing wheel size	mm	∅84×70(Double wheels)
Balance wheel size	mm	-
Dimension		
Min.fork lowered height	mm	85
Max.fork lifting height	mm	205
Max.lifting height	mm	120
Overall fork width	mm	550/685
Inside width between forks	mm	230/365
Fork length	mm	1150/1200
Fork width	mm	160
Fork thickness	mm	75
Overall length	mm	1707
Overall width	mm	697
Overall height(With handle)	mm	1181
Overall height(Without handle)	mm	714
Min.Turning radius	mm	1547
Min.Aisle width for pallets 800×1200	mm	1920
Min.Aisle width for pallets 1000×1200	mm	1953
Performance		
Travel speed,laden/unladen	km/h	3/3.5
Lift speed,laden/unladen	mm/s	35/40
Lowering speed,laden/unladen	mm/s	45/40
Gradeability,laden/unladen	%	5/7
Electrical configuration		
Drive motor	kW	DC 0.63
Lift motor	kW	DC 0.8
Battery voltage / capacity	V/Ah	24/85
Brake		Electromagnetic/Regenerative
Controller		HELI(Option CURTIS)
Weight		
Battery weight	kg	48
Service weight with battery	kg	268

* Details of specifications and equipment are based on information available at time of printing and may change without notice.

