

# HELI

**GEAR**  
Keeps you going

## **CBD15-170H** Electric Pallet Truck

### **Configuration and performance**

- Fork fit for double-deck pallet.
- Permanent magnet drive motor, compact structure, easy maintenance.
- Battery open design, easy to replacement.
- Built-in charge is standard.
- Emergency reversing device and emergency brake switch.
- Compact body, suitable for narrow space.
- Free of maintenance battery is safe operation and no pollution.
- Low noise, low energy consumption.
- Metal shell has high strength, safer.



Feature		
Model		CBD15-170H
Loading capacity	kg	1500
Load center	mm	600
Wheel base	mm	1303
Operating type		Walkie
Wheels		
Wheels type		PU
Wheel quantity Driving wheel/Balance wheel/Bearing wheel		φ210*70
Driving wheel size	mm	φ80*17
Bearing wheel size	mm	φ84*70
Balance wheel size	mm	1/2/4
Dimension		
Min.fork lowered height	mm	85
Max.fork lifting height	mm	205
Max.lifting height	mm	120
Overall fork width	mm	550/685
Inside width between forks	mm	230/365
Fork length	mm	1150/1200
Fork width	mm	160
Fork thickness	mm	75
Overall length	mm	1826
Overall width	mm	698
Overall height(With handle)	mm	1294
Overall height(Without handle)	mm	648
Min.Turning radius	mm	1593
Min.Aisle width for pallets 800×1200	mm	1939
Min.Aisle width for pallets 1000×1200	mm	1972
Performance		
Travel speed,laden/unladen	km/h	3.5/4
Lift speed,laden/unladen	mm/s	35/40
Lowering speed,laden/unladen	mm/s	75/60
Gradeability,laden/unladen	%	5/7
Electrical configuration		
Drive motor/ Lift motor	kW	DC0.65/DC0.80
Battery voltage / capacity	V	24
Brake	Ah	85
Controller		CURTIS
Weight		
Battery weight	kg	48
Service weight with battery	kg	222

\* Details of specifications and equipment are based on information available at time of printing and may change without notice.

