

# HELI

**GEAR**  
Keeps you going

## **CBD20-150G** Electric Walkie Pallet Truck

### **Configuration and performance**

- Fork fit for reversible pallets.
- Separately excited motor, Strong climbing ability. Stepless speed control system, easy to operate.
- Battery open design, easy to replacement. Built-in charger.
- Sealed batteries free of maintenance, safe operation and no pollution.
- Small body, suitable for narrow space.
- Automatic lifting limit, safety, energy saving.
- Emergency reversing device and Emergency brake switch.
- Low noise, low energy consumption, Every day only 2kWh



Feature		
Model		CBD20-150G
Weight	kg	2000
Load center	mm	600
Wheel base	mm	1468/1418
Operating type		Walkie
Wheels		
Wheels type		PU
Wheel quantity driving wheel/Balance wheel /Bearing wheel		1/2/4
Driving wheel size	mm	φ228×75
Balance wheel size	mm	φ90×48
Bearing wheel size	mm	φ80×80 (double wheels) / φ80×120 (Single wheel)
Dimension		
Min.fork lowered height	mm	85
Max.fork lifting height	mm	205
Max.lifting height	mm	120
Outside width between forks	mm	550/600/650/685
Inside width between forks	mm	210/260/310/345
Fork length	mm	1150/1200
Fork width	mm	170
Fork thickness	mm	73
Overall length	mm	1780/1830
Overall width	mm	726
Overall height(With handle)	mm	1465
Overall height(Without handle)	mm	850
Min.Turning radius	mm	1587/1637
Min.Aisle width for pallets 800×1200	mm	1840/1890
Min.Aisle width for pallets 1000×1200	mm	1875/1925
Performance		
Travel speed,laden/unladen	km/h	3.5/4
Lift speed,laden/unladen	mm/s	30/35
Lowering speed,laden/unladen	mm/s	40/30
Gradeability,laden/unladen	%	5/7
Electrical configuration		
Drive motor	KW	AC0.95
Lift motor	KW	DC1.2
Steering motor	KW	—
Battery voltage / capacity	V/Ah	24V/170Ah
Brake		Electromagnetic/regenerative
Controller		CURTIS 1230
Weight		
Battery weight	kg	122
Service weight with battery	kg	532

\* Details of specifications and equipment are based on information available at time of printing and may change without notice.

